KFRN FOB1K-4LM



Compact stainless steel bench scale with special checkweighing display for even more efficient working, now with EC type approval [M]



Measurin	n er	ietam
างเธิลจนาก	U 31	งจเษาท

5,	
Adjustment options:	External calibration
Linearity:	1,500 g
Readability [d]:	500 mg
Recommended adjusting weight:	1 kg (M1)
Repeatability:	500 mg
Resolution:	3000
Stabilisation time under laboratory conditions:	2 s
Warm up time:	10 min
Weighing capacity [Max]:	1,500 kg
Weighing system:	Strain gauge
Weighing units:	g lb oz

Display

Display digit height:

2,500 cm

yes

Technical data about verification

Minimum load [Min]:	10 g
Periodic Verification for Italy:	969-112
Verification approval conforming to 2014/31/EU:	yes
Verification by KERN possible:	yes
Verification class:	III
Verification value [e]:	500 mg

Functions

Weighing with tolerance range:

Environmental conditions 95 % Maximum humidity: 35 °C Maximum operating temperature: 5°C Minimum ambient temperature: Minimum humidity: 25 % Power supply Battery: 4x1.5 V AA 230 V AC 50 Hz Input voltage: Mains adapter external Mains adapter: Mains adapter/adapter included: EURO Operating time: 48 h Service Adjustment at the location of installation: 961-247 DAkkS Certificate: 963-127 Verification: 965-227 Category Brand: KERN Category: **Balances** Product Group: Bench scale Packaging & shipping 24 h Delivery: 420 x 300 x 175 mm Dimensions packaging (WxDxH): Gross weight: 4,700 kg Net weight: 3,800 kg Shipping method: Parcel service Construction stainless steel Casing material: Dimensions housing (WxDxH): 256 x 285 x 100 mm Material weighing plate: stainless steel 248 x 198 mm Weighing surface (WxD): Piktogramme



OPTION



FACTORY



KERN FOB1K-4LM



Compact stainless steel bench scale with special checkweighing display for even more efficient working, now with EC type approval [M]