KERN CPB30K5DM

Professional model, also with EC type approval [M], counting resolution up to 60,000 points





Measuring system	
Adjustment options:	External calibration
Linearity:	10 g 20 g
Readability [d]:	5 g 10 g
Recommended adjusting weight:	20 kg (F2); 10 kg (F2)
Repeatability:	5 g 10 g
Resolution:	3 3.000
Stabilisation time under laboratory conditions:	2 s
Tare range:	29,990 kg
Warm up time:	10 min 10 min
Weighing capacity [Max]:	15 kg 30 kg
Weighing system:	Strain gauge
Weighing units:	kg
Display	

Technical data about verification	
Minimum load [Min]:	100 g
Periodic Verification for Italy:	969-112
Verification approval conforming to 2014/31/EU:	yes
Verification by KERN possible:	yes
Verification class:	III
Verification value [e]:	5 g 10 g

2 cm

Display digit height:

Counting	
Counting resolution:	60000
Mininum piece weight at piece counting (Laboratory:	500 mg
Mininum piece weight at piece counting (Normal):	5 g
Reference weight: KERN & SOHN GmbH · Ziegelei 1 · 7	yes 2336 Balingen · Germany · Tel

Functions		
Counting function:	yes	
Function to save totals:	yes	
PRE-TARE function:	yes	
Weighing with tolerance range:	yes	

Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	-10 °C
Minimum humidity:	0 %

Power supply	
Charging time:	12 h
Input voltage:	100 V - 240 V 50 / 60 Hz
Mains adapter:	Mains adapter external
Mains adapter/adapter included:	CH EURO UK US
Operating time (Backlight off):	90 h
Operating time (Backlight on):	50 h
Rechargeable battery:	Rchrg. battery optional -

Adjustment at the location of installation: 961-248		
DAkkS Certificate:	963-128	
Verification:	965-228	

Category	
Brand:	KERN
Category:	Balances
Product Group:	Counting scale

Packaging & shipping	
Delivery:	24 h
Dimensions packaging (WxDxH):	445 x 375 x 220 mm
Gross weight:	4,310 kg
Net weight:	3,410 kg
Shipping method:	Parcel service

Construction		
Casing material:	Plastic	
Dimensions device (WxDxH):	315 x 350 x 125 mm	
Dimensions housing (WxDxH):	315 x 350 x 110 mm	
Dimensions of display device (WxDxH):	315 x 350 x 130 mm	
Level indicator:	yes	
Material weighing plate:	stainless steel	
Overall dimensions mounted (WxDxH):	320 x 350 x 125 mm	

+49–(0)7433 - 99 33-0 · www.kern-sohn.com

Service

KERN CPB 30K5DM



Professional model, also with EC type approval [M], counting resolution up to 60,000 points

Revolving screw feet: yes

Weighing surface (WxD): 295 x 225 mm

Piktogramme

STANDARD















OPTION



FACTORY

