KERN EOC 30K-3



Robust and high-resolution platform scale with practical Flip/Flop display device for greatest ease of use



Measuring system

Adjustment options:	External calibration
Linearisation (points):	3
Linearity:	15 g 30 g
Load cell connection:	4-wire
Readability [d]:	5g 10g
Recommended adjusting weight:	30 kg (M1)
Repeatability:	5g 10g
Resolution:	3 3.500
Stabilisation time under laboratory conditions:	2 s
Tare range:	-300 kg
Warm up time:	10 min 10 min
Weighing capacity [Max]:	15 kg 35 kg
Weighing system:	Strain gauge
Weighing units:	g HJ kg lb oz PCS tJ

Display

Display digit height:	2,500 cm
Display digit height:	2,500 cm

Counting

U	
Counting resolution:	35000
Mininum piece weight at piece counting (Laboratory:	1 g
Mininum piece weight at piece counting (Normal):	10 g

Functions

Counting function:	yes	
Percentage determination:	yes	
Vibration-free weighing (Animal weighing program):	yes	
Weighing with tolerance range:	yes	

Environmental conditions					
Maximum humidity:	80 %				
Maximum operating temperature:	40 °C				
Minimum ambient temperature:	-10 °C				
Minimum humidity:	0 %				
Power supply					
Charging time:	3 h				
Input voltage:	100V-240V 0.4A				
Mains adapter:	Mains adapter external				
Mains adapter/adapter included:	CH EURO UK US				
Operating time:	100 h				
Operating time (Backlight off):	43 h				
Operating time (Backlight on):	26 h				
Rechargeable battery:	Rchrg. battery optional - intern				
Service					
Adjustment at the location of installation	n: 961-248				
DAkkS Certificate:	963-128				
Category					
	KERN				
Brand:	KERN				
Brand: Category:	KERN Balances				
Category:	Balances				
Category: Product Group:	Balances				
Category: Product Group: Packaging & shipping	Balances Industiral scale				
Category: Product Group: Packaging & shipping Delivery:	Balances Industiral scale 24 h				
Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH):	Balances Industiral scale 24 h 710 x 360 x 180 mm				
Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight:	Balances Industiral scale 24 h 710 x 360 x 180 mm 7,500 kg				
Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight:	Balances Industiral scale 24 h 710 x 360 x 180 mm 7,500 kg 5,200 kg				
Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method:	Balances Industiral scale 24 h 710 x 360 x 180 mm 7,500 kg 5,200 kg				
Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction	Balances Industiral scale 24 h 710 x 360 x 180 mm 7,500 kg 5,200 kg Parcel service				
Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Dimensions of display device	Balances Industiral scale 24 h 710 x 360 x 180 mm 7,500 kg 5,200 kg Parcel service 3 m				
Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate	Balances Industiral scale 24 h 710 x 360 x 180 mm 7,500 kg 5,200 kg Parcel service 3 m 268 x 115 x 80 mm				
Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH):	Balances Industiral scale 24 h 710 x 360 x 180 mm 7,500 kg 5,200 kg Parcel service 3 m 268 x 115 x 80 mm 300 x 300 x 110 mm				
Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH): of stand:	Balances Industiral scale 24 h 710 x 360 x 180 mm 7,500 kg 5,200 kg Parcel service 3 m 268 x 115 x 80 mm 300 x 300 x 110 mm 33 cm				
Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH): of stand: Level indicator:	Balances Industiral scale 24 h 710 x 360 x 180 mm 7,500 kg 5,200 kg Parcel service 3 m 268 x 115 x 80 mm 300 x 300 x 110 mm 33 cm yes				
Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH): of stand: Level indicator: Material weighing plate:	Balances Industiral scale 24 h 710 x 360 x 180 mm 7,500 kg 5,200 kg Parcel service 3 m 268 x 115 x 80 mm 300 x 300 x 110 mm 33 cm yes stainless steel				

KERN EOC 30K-3



Robust and high-resolution platform scale with practical Flip/Flop display device for greatest ease of use

Piktogramme

STANDARD

	• 888. •	KCP	GLP		%	-√+ ⊙ 🤊)	^-
CAL EXT	RS 232	PROTOCOL	PRINTER	PCS	PERCENT		MOVE
666	B						
IP 65	MULTI	DMS	1 DAY				

OPTION

	DAkkS
ACCU	+3 DAYS