KERN EOC6K-3



Robust and high-resolution platform scale with practical Flip/Flop display device for greatest ease of use



Measuring system

Adjustment options:	External calibration			
Linearisation (points):	3			
Linearity:	3g 6g			
Load cell connection:	4-wire			
Readability [d]:	1 g 2 g			
Recommended adjusting weight:	6 kg (M1)			
Repeatability:	1 g 2 g			
Resolution:	3 3.000			
Stabilisation time under laboratory conditions:	2 s			
Tare range:	-6 kg			
Warm up time:	10 min 10 min			
Weighing capacity [Max]:	3 kg 6 kg			
Weighing system:	Strain gauge			
Weighing units:	g HJ kg lb oz PCS tJ			

Display

Display digit height:	2,500 cm
Display digit height:	2,500 cm

Counting

Counting resolution:	24000
Mininum piece weight at piece counting (Laboratory:	250 mg
Mininum piece weight at piece counting (Normal):	2,500 g

Functions

Counting function:	yes	
Percentage determination:	yes	
Vibration-free weighing (Animal weighing program):	yes	
Weighing with tolerance range:	yes	

Environmental conditions				
Maximum humidity:	80 %			
Maximum operating temperature:	40 °C			
Minimum ambient temperature:	-10 °C			
Minimum humidity:	0 %			
Power supply				
Charging time:	3 h			
Input voltage:	100V-240V 0.4A			
Mains adapter:	Mains adapter external			
Mains adapter/adapter included:	CH EURO UK US			
Operating time:	100 h			
Operating time (Backlight off):	43 h			
Operating time (Backlight on):	26 h			
Rechargeable battery:	Rchrg. battery optional - intern			
Service				
Adjustment at the location of installatio	n:961-248			
DAkkS Certificate:	963-128			
Category				
Brand:	KERN			
Category:	Balances			
Category: Product Group:				
	Balances			
Product Group:	Balances			
Product Group: Packaging & shipping	Balances Industiral scale			
Product Group: Packaging & shipping Delivery:	Balances Industiral scale 24 h			
Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH):	Balances Industiral scale 24 h 560 x 400 x 160 mm			
Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight:	Balances Industiral scale 24 h 560 x 400 x 160 mm 7,500 kg			
Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight:	Balances Industiral scale 24 h 560 x 400 x 160 mm 7,500 kg 5,200 kg			
Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method:	Balances Industiral scale 24 h 560 x 400 x 160 mm 7,500 kg 5,200 kg			
Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction	Balances Industiral scale 24 h 560 x 400 x 160 mm 7,500 kg 5,200 kg Parcel service			
Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Dimensions of display device	Balances Industiral scale 24 h 560 x 400 x 160 mm 7,500 kg 5,200 kg Parcel service 3 m			
Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate	Balances Industiral scale 24 h 560 x 400 x 160 mm 7,500 kg 5,200 kg Parcel service 3 m 268 x 115 x 80 mm			
Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH):	Balances Industiral scale 24 h 560 x 400 x 160 mm 7,500 kg 5,200 kg Parcel service 3 m 268 x 115 x 80 mm 300 x 300 x 110 mm			
Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH): of stand:	Balances Industiral scale 24 h 560 x 400 x 160 mm 7,500 kg 5,200 kg Parcel service 3 m 268 x 115 x 80 mm 300 x 300 x 110 mm 33 cm			
Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH): of stand: Level indicator:	Balances Industiral scale 24 h 560 x 400 x 160 mm 7,500 kg 5,200 kg Parcel service 3 m 268 x 115 x 80 mm 300 x 300 x 110 mm 33 cm yes			
Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH): of stand: Level indicator: Material weighing plate:	Balances Industiral scale 24 h 560 x 400 x 160 mm 7,500 kg 5,200 kg Parcel service 3 m 268 x 115 x 80 mm 300 x 300 x 110 mm 33 cm yes stainless steel			
Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH): of stand: Level indicator: Material weighing plate: Revolving screw feet:	Balances Industiral scale 24 h 560 x 400 x 160 mm 7,500 kg 5,200 kg Parcel service 3 m 268 x 115 x 80 mm 300 x 300 x 110 mm 33 cm yes stainless steel yes			

KERN EOC6K-3



Robust and high-resolution platform scale with practical Flip/Flop display device for greatest ease of use

Piktogramme

STANDARD

	• 888.•	KCP	GLP			%	-√+ ⊙ 🤊)	^
CAL EXT	RS 232	PROTOCOL	PRINTER	PCS	SUM	PERCENT	TOL	MOVE
•••	B							
IP 65	MULTI	DMS	1 DAY					

OPTION

)	DAkkS
ACCU	+3 DAYS