KERN FXN10K-3M

Bench scale, protected by stainless steel and IP68 rating, now also with EC type approval [M]





Measuring system	
Adjustment options:	External calibration
Linearity:	5 g
Readability [d]:	5 g
Recommended adjusting weight:	15 kg (M1)
Repeatability:	5 g
Resolution:	3000
Stabilisation time under laboratory conditions:	2 s
Tare range:	-15 kg
Warm up time:	10 min
Weighing capacity [Max]:	15 kg
Weighing system:	Strain gauge

Display

Display digit height: 2,500 cm

Technical data about verification	
Minimum load [Min]:	100 g
Periodic Verification for Italy:	969-112
Verification approval conforming to 2014/31/EU:	yes
Verification by KERN possible:	yes
Verification class:	III
Verification value [e]:	5 g

Counting	
Counting resolution:	7500
Mininum piece weight at piece counting (Laboratory:	2 g

Mininum piece weight at piece	20 g
counting (Normal):	

Functions		
Counting function:	yes	
SLEEP function:	yes	
Weighing with tolerance range:	yes	

Environmental conditions	
Maximum humidity:	95 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	-10 °C
Minimum humidity:	25 %

Power supply	
Battery:	4x1.5 V Size D
Operating time:	500 h

Service		
Adjustment at the location of in	stallation: 961-248	
DAkkS Certificate:	963-128	
Verification:	965-228	

Category		
Brand:	KERN	
Category:	Balances	
Product Group:	Bench scale	

Packaging & shipping	
Delivery:	24 h
Dimensions packaging (WxDxH):	325 x 365 x 225 mm
Gross weight:	3,775 kg
Net weight:	3,160 kg
Shipping method:	Parcel service

Construction	
Dimensions housing (WxDxH):	240 x 280 x 120 mm
Level indicator:	yes
Material weighing plate:	stainless steel
Overall dimensions mounted (WxDxH):	240 x 280 x 120 mm
Revolving screw feet:	yes
Weighing surface (WxD):	236 x 195 mm

KERN FXN10K-3M



Bench scale, protected by stainless steel and IP68 rating, now also with EC type approval [M]

Piktogramme STANDARD LALEXT PCS UNIT TOL IP 68 BATT DMS 1 DAY OPTION DAKKS +3 DAYS FACTORY