KERN IFB 100K-3L



High-resolution scale in heavy version with EC type approval [M], now also up to [Max] 600 kg



| Measuring system | |
|---|----------------------|
| Adjustment options: | External calibration |
| Linearity: | 20 g |
| Load cell connection: | 4-wire |
| Readability [d]: | 5 g |
| Recommended adjusting weight: | 150 kg (F2) |
| Repeatability: | 5 g |
| Resolution: | 30000 |
| Stabilisation time under laboratory conditions: | 2 s |
| Tare range: | -150 kg |
| Warm up time: | 2 h |
| Weighing capacity [Max]: | 150 kg |
| Weighing system: | Strain gauge |
| Weighing units: | kg |
| Display | |

| Display digit height: | 5,200 cm | |
|---|----------|--|
| Counting | | |
| Counting resolution: | 30000 | |
| Mininum piece weight at piece counting (Laboratory: | 5 g | |
| Mininum piece weight at piece counting (Normal): | 50 g | |
| | | |

| Functions | | |
|--|-----|--|
| Counting function: | yes | |
| Function to save totals: | yes | |
| Vibration-free weighing (Animal weighing program): | yes | |
| Weighing with tolerance range: | yes | |

| Environmental conditions | |
|--------------------------------|--------|
| Maximum humidity: | 80 % |
| Maximum operating temperature: | 40 °C |
| Minimum ambient temperature: | -10 °C |
| Minimum humidity: | 0 % |
| | |

| Power supply | |
|---------------------------------|-----------------------------------|
| Charging time: | 12 h |
| Input voltage: | 100 V - 240 V 50 / 60 Hz |
| Mains adapter: | Mains adapter external |
| Mains adapter/adapter included: | CH EURO UK US |
| Operating time (Backlight off): | 35 h |
| Operating time (Backlight on): | 8 h |
| Rechargeable battery: | Rchrg. battery optional (factory) |

| Service | | |
|-------------------------------|-----------------------|--|
| Adjustment at the location of | installation: 961-249 | |
| DAkkS Certificate: | 963-129 | |
| Catagony | | |

| Category | |
|----------------|------------------|
| Brand: | KERN |
| Category: | Balances |
| Product Group: | Industiral scale |
| | |

| Packaging & snipping | |
|-------------------------------|---------------------|
| Delivery: | 24 h |
| Dimensions packaging (WxDxH): | 680 x 1045 x 245 mm |
| Gross weight: | 24,100 kg |
| Net weight: | 20 kg |
| Shipping method: | Parcel service |

| Construction | |
|---------------------------------------|--------------------|
| Cable length of display device: | 3 m |
| Casing material: | Plastic |
| Dimensions of display device (WxDxH): | 250 x 160 x 58 mm |
| Dimensions of weighing plate (WxDxH): | 650 x 500 x 142 mm |
| of stand: | 60 cm |
| Level indicator: | yes |
| Material weighing plate: | stainless steel |
| Overall dimensions mounted (WxDxH): | 810 x 500 x 820 mm |
| Revolving screw feet: | yes |
| Wall mount: | yes |
| Weighing surface (WxD): | 650 x 500 mm |

KERN IFB 100K-3L



High-resolution scale in heavy version with EC type approval [M], now also up to [Max] 600 kg

Piktogramme

STANDARD



OPTION



FACTORY

