KERN IFB 150K20DM



High-resolution scale in heavy version with EC type approval [M], now also up to [Max] 600 kg



Measuring system	
Adjustment options:	External calibration
Linearity:	20 g 50 g
Load cell connection:	6-wire
Readability [d]:	20 g 50 g
Recommended adjusting weight:	150 kg (M1)
Repeatability:	20 g 50 g
Resolution:	3 3.000
Stabilisation time under laboratory conditions:	2 s
Tare range:	-150 kg
Warm up time:	10 min 10 min
Weighing capacity [Max]:	60 kg 150 kg
Weighing system:	Strain gauge
Weighing units:	kg

Display

Display digit height: 5,200 cm

Technical data about verification		
Minimum load [Min]:	400 g 1000 g	
Periodic Verification for Italy:	969-112	
Verification approval conforming to 2014/31/EU:	yes	
Verification by KERN possible:	yes	
Verification class:	III	
Verification value [e]:	20 g 50 g	

Counting	
Counting resolution:	30000
Mininum piece weight at piece counting (Laboratory:	5 g
Mininum piece weight at piece counting (Normal):	50 g

Functions		
Counting function:	yes	
Function to save totals:	yes	
Vibration-free weighing (Animal weighing program):	yes	
Weighing with tolerance range:	yes	

Environmental conditions		
Maximum humidity:	80 %	
Maximum operating temperature:	40 °C	
Minimum ambient temperature:	-10 °C	
Minimum humidity:	0 %	

Power supply	
Charging time:	12 h
Input voltage:	100 V - 240 V 50 / 60 Hz
Mains adapter:	Mains adapter external
Mains adapter/adapter included:	CH EURO UK US
Operating time (Backlight off):	35 h
Operating time (Backlight on):	8 h
Rechargeable battery:	Rchrg. battery optional (factory)

Adjustment at the location of installation: 961-249 DAkkS Certificate: 963-129	Service		
DAkkS Certificate: 963-129	Adjustment at the location of insta	allation: 961-249	
	DAkkS Certificate:	963-129	
Verification: 965-229	Verification:	965-229	

Category	
Brand:	KERN
Category:	Balances
Product Group:	Industiral scale

Packaging & snipping	
Delivery:	24 h
Dimensions packaging (WxDxH):	555 x 925 x 215 mm
Gross weight:	15,700 kg
Net weight:	13,500 kg
Shipping method:	Parcel service

Construction	
Cable length of display device:	3 m
Casing material:	Plastic
Dimensions of display device (WxDxH):	250 x 160 x 58 mm
Dimensions of weighing plate (WxDxH):	500 x 400 x 130 mm

KERN & SOHN GmbH · Ziegelei 1 · 72336 Balingen · Germany · Tel. +49–(0)7433 - 99 33-0 · www.kern-sohn.com

KERN IFB 150K20DM



High-resolution scale in heavy version with EC type approval [M], now also up to [Max] $600 \, \mathrm{kg}$

of stand: 60 cm

Level indicator: yes

Material weighing plate: stainless steel

Overall dimensions mounted 660 x 400 x 760 mm
(WxDxH):

Revolving screw feet: yes

Wall mount: yes

Weighing surface (WxD): 500 x 400 mm

Piktogramme

STANDARD



OPTION



FACTORY

