## KERN IFB15K2DLM



High-resolution scale in heavy version with EC type approval [M], now also up to [Max] 600  $\,\rm kg$ 



### Measuring system

Nicdouring System			
Adjustment options:	External calibration		
Linearity:	2 g   5 g		
Load cell connection:	6-wire		
Readability [d]:	2 g   5 g		
Recommended adjusting weight:	15 kg (F2)		
Repeatability:	2 g   5 g		
Resolution:	3 3.000		
Stabilisation time under laboratory conditions:	2 s		
Tare range:	-15 kg		
Warm up time:	10 min   10 min		
Weighing capacity [Max]:	6 kg   15 kg		
Weighing system:	Strain gauge		
Weighing units:	kg		
Display			
Display digit height:	5,200 cm		
Technical data about verification			
Minimum load [Min]:	40 g   100 g		
Periodic Verification for Italy:	969-112		
Verification approval conforming to 2014/31/EU:	yes		
Verification by KERN possible:	yes		
Verification class:			
Verification value [e]:	2 g   5 g		
Counting			
Counting resolution:	30000		
Mininum piece weight at piece counting (Laboratory:	500 mg		
Mininum piece weight at piece	5 g		

Functions			
Counting function:	yes		
Function to save totals:	yes		
Vibration-free weighing (Animal weighing program):	yes		
Weighing with tolerance range:	yes		
Environmental conditions			
Maximum humidity:	80 %		
Maximum operating temperature:	40 °C		
Minimum ambient temperature:	-10 °C		
Minimum humidity:	0 %		
Power supply			
Charging time:	12 h		
Input voltage:	100 V - 240 V 50 / 60 Hz		
Mains adapter:	Mains adapter external		
Mains adapter/adapter included:	CH EURO UK US		
Operating time (Backlight off):	35 h		
Operating time (Backlight on):	8 h		
Rechargeable battery:	Rchrg. battery optional (factory)		
Service			
Adjustment at the location of installation	on:961-248		
DAkkS Certificate:	963-128		
Verification:	965-228		
Category			
Brand:	KERN		
Category:	Balances		
Product Group:			
	Industiral scale		
Packaging & shipping	Industiral scale		
	Industiral scale		
Packaging & shipping			
Packaging & shipping Delivery:	24 h		
Packaging & shipping Delivery: Dimensions packaging (WxDxH):	24 h 470 x 800 x 240 mm		
Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight:	24 h 470 x 800 x 240 mm 12 kg		
Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight:	24 h 470 x 800 x 240 mm 12 kg 9,800 kg		
Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method:	24 h 470 x 800 x 240 mm 12 kg 9,800 kg		
Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction	24 h 470 x 800 x 240 mm 12 kg 9,800 kg Parcel service		
Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device:	24 h 470 x 800 x 240 mm 12 kg 9,800 kg Parcel service 3 m		
Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Casing material: Dimensions of display device	24 h 470 x 800 x 240 mm 12 kg 9,800 kg Parcel service 3 m Plastic		

counting (Normal): KERN & SOHN GmbH · Ziegelei 1 · 72336 Balingen · Germany · Tel. +49–(0)7433 - 99 33-0 · www.kern-sohn.com

# KERN IFB15K2DLM

High-resolution scale in heavy version with EC type approval [M], now also up to [Max] 600 kg



of stand:	60 cm	
Level indicator:	yes	
Material weighing plate:	stainless steel	
Overall dimensions mounted (WxDxH):	560 x 300 x 490 mm	
Revolving screw feet:	yes	
Wall mount:	yes	
Weighing surface (WxD):	400 x 300 mm	

### Piktogramme

#### STANDARD



OPTION

DAkkS +3 DAYS

FACTORY

8	D⁄A	E C C C C C C C C C C C C C C C C C C C	Μ
BT 2.0	ANALOG	ACCU	+3 DAYS