# KERN IFB 300K-2



High-resolution scale in heavy version with EC type approval [M], now also up to [Max] 600 kg



Measuring system	
Adjustment options:	External calibration
Linearity:	40 g
Load cell connection:	6-wire
Readability [d]:	10 g
Recommended adjusting weight:	300 kg (F2)
Repeatability:	10 g
Resolution:	30000
Stabilisation time under laboratory conditions:	2 s
Tare range:	-300 kg
Warm up time:	2 h
Weighing capacity [Max]:	300 kg
Weighing system:	Strain gauge
Weighing units:	kg

Display digit height:	5,200 cm
Counting	
Counting resolution:	30000
Mininum piece weight at piece counting (Laboratory:	10 g
Mininum piece weight at piece counting (Normal):	100 g

Functions	
Counting function:	yes
Function to save totals:	yes
Vibration-free weighing (Animal weighing program):	yes
Weighing with tolerance range:	yes

Maximum humidity: 80 %	
•	
Maximum operating temperature: 40 °C	
Minimum ambient temperature: -10 °C	
Minimum humidity: 0 %	

Power supply	
Charging time:	12 h
Input voltage:	100 V - 240 V 50 / 60 Hz
Mains adapter:	Mains adapter external
Mains adapter/adapter included:	CH EURO UK US
Operating time (Backlight off):	35 h
Operating time (Backlight on):	8 h
Rechargeable battery:	Rchrg. battery optional (factory)

Service		
Adjustment at the location of	installation: 961-249	
DAkkS Certificate:	963-129	
Category		

Brand:	KERN	
Category:	Balances	
Product Group:	Industiral scale	
Packaging & shipping		

i dokaging a shipping	
Delivery:	24 h
Dimensions packaging (WxDxH):	675 x 1050 x 250 mm
Gross weight:	24,900 kg
Net weight:	20 kg
Shipping method:	Parcel service

Construction	
Cable length of display device:	3 m
Casing material:	Plastic
Dimensions of display device (WxDxH):	250 x 160 x 58 mm
Dimensions of weighing plate (WxDxH):	650 x 500 x 142 mm
of stand:	60 cm
Level indicator:	yes
Material weighing plate:	stainless steel
Overall dimensions mounted (WxDxH):	810 x 500 x 820 mm
Revolving screw feet:	yes
Wall mount:	yes
Weighing surface (WxD):	650 x 500 mm

## KERN IFB 300K-2



High-resolution scale in heavy version with EC type approval [M], now also up to [Max] 600  $\,$  kg  $\,$ 

### Piktogramme

#### STANDARD



#### **OPTION**



#### **FACTORY**

