KERN IFB 30K-3



High-resolution scale in heavy version with EC type approval [M], now also up to [Max] 600 kg



Measuring system	
Adjustment options:	External calibration
Linearity:	4 g
Load cell connection:	6-wire
Readability [d]:	1 g
Recommended adjusting weight:	30 kg (F2)
Repeatability:	1 g
Resolution:	30000
Stabilisation time under laboratory conditions:	2 s
Tare range:	-30 kg
Warm up time:	2 h
Weighing capacity [Max]:	30 kg
Weighing system:	Strain gauge
Weighing units:	kg

Display digit height:	5,200 cm
Counting	
Counting resolution:	30000
Mininum piece weight at piece counting (Laboratory:	1 g
Mininum piece weight at piece counting (Normal):	10 g

Display

Functions		
Counting function:	yes	
Function to save totals:	yes	
Vibration-free weighing (Animal weighing program):	yes	
Weighing with tolerance range:	yes	

Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	-10 °C
Minimum humidity:	0 %

Power supply	
Charging time:	12 h
Input voltage:	100 V - 240 V 50 / 60 Hz
Mains adapter:	Mains adapter external
Mains adapter/adapter included:	CH EURO UK US
Operating time (Backlight off):	35 h
Operating time (Backlight on):	8 h
Rechargeable battery:	Rchrg. battery optional (factory)

Service	
Adjustment at the location of ins	stallation: 961-248
DAkkS Certificate:	963-128
Category	
Brand:	KERN

Category:

Product Group:

Packaging & shipping	
Delivery:	24 h
Dimensions packaging (WxDxH):	465 x 795 x 230 mm
Gross weight:	11,930 kg
Net weight:	9,705 kg
Shipping method:	Parcel service

Balances

Industiral scale

Construction	
Cable length of display device:	3 m
Casing material:	Plastic
Dimensions of display device (WxDxH):	250 x 160 x 58 mm
Dimensions of weighing plate (WxDxH):	400 x 300 x 128 mm
of stand:	60 cm
Level indicator:	yes
Material weighing plate:	stainless steel
Overall dimensions mounted (WxDxH):	5500 x 300 x 260 mm
Revolving screw feet:	yes
Wall mount:	yes
Weighing surface (WxD):	400 x 300 mm

KERN IFB 30K-3



High-resolution scale in heavy version with EC type approval [M], now also up to [Max] 600 $\,$ kg $\,$

Piktogramme

STANDARD



OPTION



FACTORY

