KERN IFB 600K-2



High-resolution scale in heavy version with EC type approval [M], now also up to [Max] 600 kg



| Adjustment options: | External calibration |
|---|----------------------|
| Linearity: | 60 g |
| Load cell connection: | 6-wire |
| Readability [d]: | 20 g |
| Recommended adjusting weight: | 600 kg (F2) |
| Repeatability: | 20 g |
| Resolution: | 30000 |
| Stabilisation time under laboratory conditions: | 2 s |
| Tare range: | -600 kg |
| Warm up time: | 2 h |
| Weighing capacity [Max]: | 600 kg |
| Weighing system: | Strain gauge |
| Weighing units: | kg |

| Display digit height: | 5,200 cm |
|---|----------|
| Counting | |
| Counting resolution: | 30000 |
| Mininum piece weight at piece counting (Laboratory: | 20 g |
| Mininum piece weight at piece counting (Normal): | 200 g |
| | |

| Functions | |
|--|-----|
| Counting function: | yes |
| Function to save totals: | yes |
| Vibration-free weighing (Animal weighing program): | yes |
| Weighing with tolerance range: | yes |

| Environmental conditions | |
|--------------------------------|--------|
| Maximum humidity: | 80 % |
| Maximum operating temperature: | 40 °C |
| Minimum ambient temperature: | -10 °C |
| Minimum humidity: | 0 % |

| Power supply | |
|---------------------------------|-----------------------------------|
| Charging time: | 12 h |
| Input voltage: | 100 V - 240 V 50 / 60 Hz |
| Mains adapter: | Mains adapter external |
| Mains adapter/adapter included: | CH EURO UK US |
| Operating time (Backlight off): | 35 h |
| Operating time (Backlight on): | 8 h |
| Rechargeable battery: | Rchrg. battery optional (factory) |

| Service | |
|-------------------------------|--------------------------|
| Adjustment at the location of | of installation: 961-250 |
| DAkkS Certificate: | 963-130 |
| Category | |
| Brand: | KERN |

Balances

Industiral scale

Category:

Product Group:

| Packaging & shipping | |
|-------------------------------|---------------------|
| Delivery: | 48 h |
| Dimensions packaging (WxDxH): | 1250 x 800 x 380 mm |
| Gross weight: | 70 kg |
| Net weight: | 65 kg |
| Shipping method: | Freight forwarder |

| Construction | |
|---------------------------------------|--------------------|
| Cable length of display device: | 3 m |
| Casing material: | Plastic |
| Dimensions of display device (WxDxH): | 250 x 160 x 58 mm |
| Dimensions of weighing plate (WxDxH): | 800 x 600 x 200 mm |
| Level indicator: | yes |
| Material weighing plate: | stainless steel |
| Overall dimensions mounted (WxDxH): | 800 x 600 x 190 mm |
| Revolving screw feet: | yes |
| Wall mount: | yes |
| Weighing surface (WxD): | 800 x 600 mm |

KERN IFB 600K-2



High-resolution scale in heavy version with EC type approval [M], now also up to [Max] 600 $\,$ kg $\,$

Piktogramme

STANDARD



OPTION



FACTORY

