KERN IFB 60K-3



High-resolution scale in heavy version with EC type approval [M], now also up to [Max] 600 kg



Measuring system	
Adjustment options:	External calibration
Linearity:	8 g
Load cell connection:	6-wire
Readability [d]:	2 g
Recommended adjusting weight:	60 kg (F2)
Repeatability:	2 g
Resolution:	30000
Stabilisation time under laboratory conditions:	2 s
Tare range:	-60 kg
Warm up time:	2 h
Weighing capacity [Max]:	60 kg
Weighing system:	Strain gauge
Weighing units:	kg

Display digit height:	5,200 cm
Counting	
Counting resolution:	60000
Mininum piece weight at piece counting (Laboratory:	1 g
Mininum piece weight at piece counting (Normal):	10 g

Display

Functions	
Counting function:	yes
Function to save totals:	yes
Vibration-free weighing (Animal weighing program):	yes
Weighing with tolerance range:	yes

Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	-10 °C
Minimum humidity:	0 %

Power supply	
Charging time:	12 h
Input voltage:	100 V - 240 V 50 / 60 Hz
Mains adapter:	Mains adapter external
Mains adapter/adapter included:	CH EURO UK US
Operating time (Backlight off):	35 h
Operating time (Backlight on):	8 h
Rechargeable battery:	Rchrg. battery optional (factory)

Service		
Adjustment at the location of ins	stallation: 961-249	
DAkkS Certificate:	963-129	
Category		
Brand:	KERN	

Product Group:	Industiral scale
Packaging & shipping	
Delivery:	24 h
Dimensions packaging (WxDxH):	470 x 800 x 220 mm
Gross weight:	12 kg
Net weight:	9,700 kg

Balances

Parcel service

Category:

Shipping method:

Construction	
Cable length of display device:	3 m
Casing material:	Plastic
Dimensions of display device (WxDxH):	250 x 160 x 58 mm
Dimensions of weighing plate (WxDxH):	400 x 300 x 128 mm
of stand:	60 cm
Level indicator:	yes
Material weighing plate:	stainless steel
Overall dimensions mounted (WxDxH):	400 x 300 x 120 mm
Revolving screw feet:	yes
Wall mount:	yes
Weighing surface (WxD):	400 x 300 mm

KERN IFB 60K-3



High-resolution scale in heavy version with EC type approval [M], now also up to [Max] 600 $\,$ kg $\,$

Piktogramme

STANDARD



OPTION



FACTORY

