# KERN IFB6K-4S



High-resolution scale in heavy version with EC type approval [M], now also up to [Max] 600 kg



### Measuring system

Medouling System				
Adjustment options:	External calibration			
Linearity:	600 mg			
Load cell connection:	4-wire			
Readability [d]:	200 mg			
Recommended adjusting weight:	6 kg (F2)			
Repeatability:	200 mg			
Resolution:	30000			
Stabilisation time under laboratory conditions:	2 s			
Tare range:	-6 kg			
Warm up time:	2 h			
Weighing capacity [Max]:	6 kg			
Weighing system:	Strain gauge			
Weighing units:	kg			
Display				
Display digit height:	5,200 cm			
Counting				
Counting resolution:	30000			
Mininum piece weight at piece counting (Laboratory:	200 mg			
Mininum piece weight at piece counting (Normal):	2 g			
Functions				
Counting function:	yes			
Function to save totals:	yes			
Vibration-free weighing (Animal weighing program):	yes			
Weighing with tolerance range:	yes			

Environmental conditions				
Maximum humidity:	80 %			
Maximum operating temperature:	40 °C			
Minimum ambient temperature:	-10 °C			
Minimum humidity:	0 %			
Power supply				
Charging time:	12 h			
Input voltage:	100 V - 240 V 50 / 60 Hz			
Mains adapter:	Mains adapter external			
Mains adapter/adapter included:	CH EURO UK US			
Operating time (Backlight off):	35 h			
Operating time (Backlight on):	8 h			
Rechargeable battery:	Rchrg. battery optional (factory)			
Service				
Adjustment at the location of installati	on:961-248			
DAkkS Certificate:	963-128			
Category				
Brand:	KERN			
Category:	Balances			
Product Group:	Industiral scale			
Packaging & shipping				
Delivery:	24 h			
Dimensions packaging (WxDxH):	415 x 700 x 240 mm			
Gross weight:	7,030 kg			
Net weight:	5,150 kg			
Shipping method:	Parcel service			
Construction				
Cable length of display device:	3 m			
Casing material:	Plastic			
Dimensions of display device (WxDxH):	250 x 160 x 58 mm			
Dimensions of weighing plate (WxDxH):	230 x 230 x 110 mm			
of stand:	3,300 m			
Level indicator:	yes			
Material weighing plate:	stainless steel			
Overall dimensions mounted (WxDxH):	230 x 230 x 360 mm			
Revolving screw feet:	yes			
Wall mount:	yes			
Weighing surface (WxD):	230 x 230 mm			

## KERN IFB6K-4S



High-resolution scale in heavy version with EC type approval [M], now also up to [Max] 600 kg

### Piktogramme

#### STANDARD

	KCP PROTOCOL	• ANA •		PCS		-√+ ⊙ 🤊 ୬	
CAL EXT	PROTOCOL	RS 232	PRINTER	PCS	SUM	TOL	MOVE
A			<b>.</b>				
MULTI	DMS	1 DAY	2 DAYS				
OPTIC	NC						
	1						
DAkkS							

+3 DAYS

### FACTORY

