KERN IOC60K-2M



All-round platform scale with a range of communication options and EC type approval [M]



Maga	surin a	system
weas		Systen
Incac	Jannig	0,0001

Adjustment options:	External calibration
Linearisation (points):	3
Linearity:	30 g 60 g
Load cell connection:	4-wire
Readability [d]:	10 g 20 g
Recommended adjusting weight:	60 kg (M1)
Repeatability:	10 g 20 g
Resolution:	3 3.000
Stabilisation time under laboratory conditions:	2 s
Tare range:	-60 kg
Warm up time:	10 min 10 min
Weighing capacity [Max]:	30 kg 60 kg
Weighing system:	Strain gauge
Weighing units:	g HJ kg lb oz PCS tJ

1 119		ωw
213	21	αv

Display digit height:	2,500 cm
Display digit height:	2,500 cm

Technical data about verification

Minimum load [Min]:	200 g 400 g
Periodic Verification for Italy:	969-112
Verification approval conforming to 2014/31/EU:	yes
Verification by KERN possible:	yes
Verification class:	III
Verification value [e]:	10 g 20 g

Counting

-		
Counting resolution:	30000	
Mininum piece weight at piece counting (Laboratory:	2 g	
Mininum piece weight at piece counting (Normal):	20 g	

Functions	
Counting function:	yes
Percentage determination:	yes
PRE-TARE function:	yes
Vibration-free weighing (Animal weighing program):	yes
Weighing with tolerance range:	yes
Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	-10 °C
Minimum humidity:	0 %
Power supply	
Charging time:	3 h
Input voltage:	100V-240V AC 50/60Hz 0,400 Amax
Mains adapter:	Mains adapter external
Mains adapter/adapter included:	EURO UK US
Operating time:	100 h
Operating time (Backlight off):	43 h
Operating time (Backlight on):	26 h
Rechargeable battery:	Rchrg. battery optional - intern
Service	
Adjustment at the location of installation	n:961-249
DAkkS Certificate:	963-129
Verification:	965-229
Category	
Brand:	KERN
Category:	Balances
Product Group:	Industiral scale
Packaging & shipping	
Delivery:	24 h
Dimensions packaging (WxDxH):	810 x 350 x 180 mm
Gross weight:	8,800 kg
Net weight:	7,600 kg
Shipping method:	Parcel service
Construction	
Cable length of display device:	3 m
Dimensions of display device (WxDxH):	268 x 115 x 80 mm
Dimensions of weighing plate (WxDxH):	400 x 300 x 110 mm
7433 - 99 33-0 · www.kern-sohn.com	1

KERN & SOHN GmbH · Ziegelei 1 · 72336 Balingen · Germany · Tel. +49–(0)7433 - 99 33-0 · www.kern-sohn.com

KERN IOC60K-2M



All-round platform scale with a range of communication options and EC type approval [M]

Level indicator:	yes
Material weighing plate:	stainless steel
Revolving screw feet:	yes
Wall mount:	yes
Weighing surface (WxD):	400 x 300 mm

Piktogramme

STANDARD

CAL EXT RS 232	KCP PROTOCOL	GLP PRINTER	PCS	SUM	% Percent	-√+ ⊙ 🤊 TOL	MOVE
IP 65	DMS	1 DAY	2 DAYS				

OPTION



FACTORY

